

Trane Rental Services

12-Ton Air Conditioner



Trane Rental Services is your all-encompassing business solutions partner. We provide scalable cooling, heating, and power options for all your temporary HVAC needs.

The 12-ton portable air conditioning unit offers unmatched versatility, providing powerful cooling solutions for a wide range of applications, from industrial spaces to large-scale events. Its portability and ease of setup make it ideal for temporary cooling needs, emergency situations, and supplemental cooling in demanding environments.

Air Conditioner Features:

- Compact Dimensions
- Plug and Play Package
- Indoor or Outdoor Installation
- Camlock Power Connections
- Digital Thermostat
- Electric Heat
- Scroll Compressors
- Onboard Condensate Pump
- Heavy Duty Casters
- Will fit thru 3' Standard Door
- Forkliftable Frame
- 12" Supply/Return Collars
- 20" Condenser Collar
- 460V/3PH/60HZ
- Stepup Transformers Available
- Dehumidification (F2 only)



SCAN ME

Trane Rental Services is available 24/7 for technical support, quotes, and inquiries regarding availability. With our round-the-clock support, we can also offer shipments on weekends, holidays, and after normal business hours.

**Technical Support, Trouble Shooting,
24/7 Emergency Dispatch**

800-755-5115

General Data			
Trane Model	RSDX0012F0	RSDX0012F1	RSDX0012F2
Manufacturer	United Coolair	Kwikool	Smart Family Products
Manufacturer Model	MACH145G4AS30	KPO12-43	SLIC12R-MS
Cooling Capacity(Tons)	12		
Compressors	1		
Compressor Type	Scroll		
Refrigerant Type	R-410 A	407C	R-134A

Cooling Data			
	RSDX0012F0	RSDX0012F1	RSDX0012F2
Cooling Capacity (BTUH)	143,000	135,000	173,400
Operation Temps	65-110°F	30-110°F 50% RH	30-115°F
Evaporator CFM	4,000	5,500	1,500-5,500
Condenser CFM	4,000	8,500	8,500
VFD	No	No	Yes

Heating Data			
	RSDX0012F0	RSDX0012F1	RSDX0012F2
Heating Capacity	30kW	24kW	16kW/32kW (optional)
Heating BTU	102,420	81,936	54,594/109,188

Duct Configuration			
	RSDX0012F0	RSDX0012F1	RSDX0012F2
Evaporator Connections	3 Supply/3 Return	2 Supply/2 Return	2 Supply/2 Return
Size	12"		
Condensor Connections	1 Supply/1 Return	1 Supply	1 Supply
Size	20"		
Min Duct Requirements	n/a	25' Supply/Return	n/a

Electrical			
	RSDX0012F0	RSDX0012F1	RSDX0012F2
Single Point Power Supply	460V/3PH/60HZ	460V/3PH/60HZ	460V/3PH/60HZ
Connection Type	Camlock	Camlock	Camlock
Cooling Amps	36.3	35	28.7
MCA w/Heat	53.2	35.32	57
MOP	60	60	60
SCCR Rating	5kA	25kA	5kA

Dimensional Data			
	RSDX0012F0	RSDX0012F1	RSDX0012F2
L x W x H	78" x 34.5" x 71"	64" x 32" x 61.5"	100" x 34.4" x 73"
Weight (lbs)	1,500	1,200	2,200



Trane – by Trane Technologies (NYSE: TT), a global climate innovator – creates comfortable, energy efficient indoor environments through a broad portfolio of heating, ventilating and air conditioning systems and controls, services, parts and supply. For more information, please visit trane.com or tranetechnologies.com.

All trademarks referenced in this document are the trademarks of their respective owners.

© 2025 Trane. All Rights Reserved.

TEMP-SLB007-EN
04/09/2025