



- 1 OPTIONAL LEAK DETECTION SENSOR PRESET ON HEAT PUMP/DUAL FUEL OR 4T & 5T UNITS WITH OPTIONAL HOT GAS REHEAT.
- 2 BLUE WIRE = INDOOR MOTOR SPEED CONTROL FOR COOLING MODE OPERATION (PINS 1-5)
ORANGE WIRE = INDOOR MOTOR SPEED CONTROL FOR HEATING MODE OPERATION (PINS 4-5)*
*MINIMUM SPEED FOR HEATING MODE OPERATION IS PIN 4. SEE INSTALLATION MANUAL FOR FAN SPEEDS CORRESPONDING TO MOTOR SPEED TAPS. TO SET INDOOR MOTOR TO THE SAME SPEED FOR COOLING AND HEATING MODE, MOVE THE BLUE WIRE TO TAP4B.
- 3 WIRING SHOWN WITH STANDARD INDOOR MOTOR SEE INSET B FOR OVERSIZED INDOOR MOTOR.

	LEGEND	
REF DES	DESCRIPTION	LINE NO
HTB3	TERM BLOCK-INDOOR FAN	67
IDM1	MOTOR-INDOOR 1-INSET B	83
IDM1	MOTOR-INDOOR 1	74
LDS-F	LEAK DETECTION SENSOR	64

TRANE®

THIS DRAWING IS PROPRIETARY AND SHALL NOT BE COPIED OR ITS CONTENTS DISCLOSED TO OUTSIDE PARTIES WITHOUT THE WRITTEN CONSENT OF TRANE.

POWER, SINGLE INDOOR FAN
COOLING ONLY/ELECTRIC HEAT, STD SCCR,
MULTI-TAP MOTOR

MASTER NUMBER:	DRAWING NUMBER:	SHEET:	REV:
	12134799	2 OF 10	A