




# Product and Submittal Data

## Split System Cooling

5TTX5018A1000A  
5TTX5024A1000A  
5TTX5030A1000A/B  
5TTX5036A1000A/B  
5TTX5042A1000A  
5TTX5048A1000A/B  
5TTX5060A1000A/B



**Note:** Graphics in this document are for representation only. Actual model may differ in appearance.



## Copyright

This document and the information in it are the property of Trane, and may not be used or reproduced in whole or in part without written permission. Trane reserves the right to revise this publication at any time, and to make changes to its content without obligation to notify any person of such revision or change.

## Trademark

All trademarks referenced in this document are the trademarks of their respective owners.

## Data Notes

This document supersedes and includes data from the documents listed below.

**Table 1. Data notes**

| Literature Number | Title   |
|-------------------|---|
| ODR-PRD019*-EN    | Split System Cooling 5TTX5 Product Data           |
| 5TTX5018A-SUB-1*  | Submittal, 1.5 Ton Split System Cooling 5TTX5018A |
| 5TTX5024A-SUB-1*  | Submittal, 2.0 Ton Split System Cooling 5TTX5024A |
| 5TTX5030A-SUB-1*  | Submittal, 2.5 Ton Split System Cooling 5TTX5030A |
| 5TTX5036A-SUB-1*  | Submittal, 3.0 Ton Split System Cooling 5TTX5036A |
| 5TTX5042A-SUB-1*  | Submittal, 3.5 Ton Split System Cooling 5TTX5042A |
| 5TTX5048A-SUB-1*  | Submittal, 4.0 Ton Split System Cooling 5TTX5048A |
| 5TTX5060A-SUB-1*  | Submittal, 5.0 Ton Split System Cooling 5TTX5060A |



# Table of Contents

|  |    |
|--|----|
| Product Specifications .....           | 4  |
| Sound Power Level .....                | 7  |
| Accessory Description and Usage .....  | 8  |
| Model Nomenclature.....                | 8  |
| Wiring Diagrams.....                   | 9  |
| Dimensional Data.....                  | 13 |
| Mechanical Specification Options ..... | 14 |



# Product Specifications

**Table 2. 5TTX5018 – 5TTX5036**

| Model No. (a) (b)                       | 5TTX5018A1000A      | 5TTX5024A1000A      | 5TTX5030A1000A/B      | 5TTX5036A1000A/B      |
|---|---------------------|---------------------|-----------------------|-----------------------|
| Power Conns. – V/Ph/Hz (c)              | 208/230/1/60        | 208/230/1/60        | 208/230/1/60          | 208/230/1/60          |
| Min. BRCH. CIR. Ampacity                | 9                   | 14                  | 15/17                 | 18                    |
| BR. CIR. PROT. RTG. – Max. (Amps)       | 20                  | 25                  | 25                    | 30                    |
| <b>Compressor</b>                       | CLIMATUFF® - SCROLL | CLIMATUFF® - SCROLL | CLIMATUFF® - SCROLL   | CLIMATUFF® - SCROLL   |
| No. Used – No. Stages                   | 1 – 1               | 1 – 1               | 1 – 1                 | 1 – 1                 |
| Volts/Ph/Hz                             | 208/230/1/60        | 208/230/1/60        | 208/230/1/60          | 208/230/1/60          |
| RL Amps <sup>(d)</sup> – LR Amps        | 6.9 – 45.1          | 10.3 – 60.1         | 12.5 – 67.1/12.7–76.1 | 13.5 – 75.1/13.5–83.1 |
| Factory Installed                       |                     |                     |                       |                       |
| Start Components (e)                    | NO                  | NO                  | NO                    | NO                    |
| Insulation/Sound Blanket                | NO                  | NO                  | NO                    | NO                    |
| Compressor Heat                         | NO                  | NO                  | NO                    | NO                    |
| <b>Outdoor Fan</b>                      | PROPELLER           | PROPELLER           | PROPELLER             | PROPELLER             |
| DIA. (in.)– No. Used                    | 23.0 – 1            | 23.0 – 1            | 23.0 – 1              | 23.0 – 1              |
| Type Drive – No. Speeds                 | DIRECT – 1          | DIRECT – 1          | DIRECT – 1            | DIRECT – 1            |
| CFM @ 0.0 IN. W.G. <sup>(f)</sup>       | 3000                | 3070                | 3250                  | 3130                  |
| No. Motors – HP                         | 1 – 1/8             | 1 – 1/8             | 1 – 1/8               | 1 – 1/8               |
| Motor Speed R.P.M.                      | 825                 | 825                 | 825                   | 825                   |
| Volts/Ph/Hz                             | 208/230/1/60        | 208/230/1/60        | 208/230/1/60          | 208/230/1/60          |
| F.L. Amps                               | 0.77                | 0.77                | 0.77                  | 0.77                  |
| <b>Outdoor Coil – Type</b>              | SPINE FIN™          | SPINE FIN™          | SPINE FIN™            | SPINE FIN™            |
| Rows – F.P.I.                           | 1 – 24              | 1 – 24              | 1 – 24                | 1 – 24                |
| Face Area (Sq. Ft.)                     | 21.25               | 18.75               | 21.25                 | 18.75                 |
| Tube Size (in.)                         | 3/8                 | 3/8                 | 3/8                   | 3/8                   |
| <b>Refrigerant</b>                      |                     |                     |                       |                       |
| LBS. – R-454B (O.D. Unit) (g)           | 3 LBS., 12 OZ       | 3 LBS., 10 OZ       | 3 LBS., 8 OZ          | 3 LBS., 8 OZ          |
| Factory Supplied                        | YES                 | YES                 | YES                   | YES                   |
| Valve Connection Size – (in.) O.D. Gas  | 3/4                 | 3/4                 | 3/4                   | 3/4                   |
| Valve Connection Size – (in.) O.D. Liq. | 5/16                | 5/16                | 5/16                  | 5/16                  |
| Line Size – (in.) O.D. Gas (h) (i)      | 3/4                 | 3/4                 | 3/4                   | 7/8                   |
| Line Size – (in.) O.D. Liq.             | 5/16                | 5/16                | 5/16                  | 5/16                  |
| <b>Charging Specifications</b>          |                     |                     |                       |                       |
| Subcooling                              | 10°F                | 10°F                | 10°F                  | 10°F                  |
| <b>Dimensions</b>                       | H X W X D           |                     |                       |                       |
| Crated (in.)                            | 47 x 30 x 33        | 43 x 30 x 33        | 47 x 30 x 33          | 43 x 30 x 33          |
| <b>Weight</b>                           |                     |                     |                       |                       |
| Shipping (lbs.)                         | 220                 | 183                 | 220                   | 183                   |
| Net (lbs.)                              | 184                 | 156                 | 184                   | 156                   |
| <b>Optional Accessories:</b>            |                     |                     |                       |                       |
| Anti-short Cycle Timer                  | TAYASCT501A         | TAYASCT501A         | TAYASCT501A           | TAYASCT501A           |
| Evaporator Defrost Control              | AY28X079            | AY28X079            | AY28X079              | AY28X079              |

**Table 2. 5TTX5018 – 5TTX5036 (continued)**

|                                    |                 |                 |                 |                 |
|------------------------------------|-----------------|-----------------|-----------------|-----------------|
| Rubber Isolator Kit                | BAYISLT101      | BAYISLT101      | BAYISLT101      | BAYISLT101      |
| Extreme Condition Mount Kit        | BAYECMT023      | BAYECMT023      | BAYECMT023      | BAYECMT004      |
| Start Kit                          | BAYKSKT263      | BAYKSKT263      | BAYKSKT263      | BAYKSKT263      |
| Crankcase Heater Kit               | BAYCCHT302      | BAYCCHT302      | BAYCCHT302      | BAYCCHT302      |
| Seacoast Kit                       | BAYSEAC001      | BAYSEAC001      | BAYSEAC001      | BAYSEAC001      |
| Low Ambient Kit                    | BAYLOAM103      | BAYLOAM103      | BAYLOAM103      | BAYLOAM103      |
| Service Valve Panel Cover          | TAYSVPANL0032AA | TAYSVPANL0032AA | TAYSVPANL0044AA | TAYSVPANL0044AA |
| Refrigerant Lineset <sup>(i)</sup> |                 |                 |                 |                 |

- (a) Certified in accordance with the Unitary Air-conditioner equipment certification program which is based on AHRI standard 210/240.
- (b) Rated in accordance with AHRI standard 270.
- (c) Calculated in accordance with N.E.C. Only use HACR circuit breakers or fuses.
- (d) This value shown for compressor RLA on the unit nameplate and on this specification sheet is used to compute minimum branch circuit ampacity and max. fuse size. The value shown is the branch circuit selection current.
- (e) Use start components only when compressor is found to enter locked rotor condition and will not start or when lights dim at compressor start. " No means no start components. Yes means quick start kit components. PTC means positive temperature coefficient starter. Optional kit shown.
- (f) Standard Air– Dry Coil– Outdoor.
- (g) This value approximate. For more precise value see unit nameplate.
- (h) Reference the outdoor unit ship-with literature for refrigerant piping length and lift guidelines. Reference the refrigerant piping software pub # 32-3312-xx or *Refrigerant Piping Manual for Small Split Cooling and Heat Pump Systems Application Guide* (SS-APG006\*-EN) for long line sets or specialty applications (xx denotes latest revision).
- (i) The outdoor condensing units are factory charged with the system charge required for the outdoor condensing unit, ten (10) feet of tested connecting line, and the smallest rated indoor evaporative coil match. Always verify proper system charge via subcooling (TXV/EV) or superheat (fixed orifice) per the unit nameplate.
- (j) 25, 30, 35 and 50 foot linesets available. For a complete listing of lineset options available from equipment or supply stores, refer to the Trane Residential and Light Commercial Product Handbook.

**Table 3. 5TTX5042 – 5TTX5060**

| <b>Model No.</b> <sup>(a) (b)</sup>   | 5TTX5042A1000A      | 5TTX5048A1000A/B          | 5TTX5060A1000A/B          |
|---------------------------------------|---------------------|---------------------------|---------------------------|
| Power Conns. – V/Ph/Hz <sup>(c)</sup> | 208/230/1/60        | 208/230/1/60              | 208/230/1/60              |
| Min. BRCH. CIR. Ampacity              | 21                  | 23/25                     | 28/30                     |
| BR. CIR. PROT. RTG. – Max. (Amps)     | 30                  | 35/45                     | 50                        |
| <b>Compressor</b>                     | CLIMATUFF® - SCROLL | CLIMATUFF® - SCROLL       | CLIMATUFF® - SCROLL       |
| No. Used – No. Stages                 | 1 – 1               | 1 – 1                     | 1 – 1                     |
| Volts/Ph/Hz                           | 208/230/1/60        | 208/230/1/60              | 208/230/1/60              |
| RL Amps <sup>(d)</sup> – LR Amps      | 14.7 – 109.1        | 17.3 – 126.1/19.6 – 118.1 | 21.8 – 143.1/23.4 – 134.1 |
| Factory Installed                     |                     |                           |                           |
| Start Components <sup>(e)</sup>       | NO                  | NO                        | NO                        |
| Insulation/Sound Blanket              | NO                  | NO                        | NO                        |
| Compressor Heat                       | NO                  | NO                        | NO                        |
| <b>Outdoor Fan</b>                    | PROPELLER           | PROPELLER                 | PROPELLER                 |
| DIA. (in.) – No. Used                 | 27.5 – 1            | 27.5 – 1                  | 27.5 – 1                  |
| Type Drive – No. Speeds               | DIRECT – 1          | DIRECT – 1                | DIRECT – 1                |
| CFM @ 0.0 IN. W.G. <sup>(f)</sup>     | 4841                | 5165                      | 5180                      |
| No. Motors – HP                       | 1 – 1/5             | 1 – 1/5                   | 1 – 1/3                   |
| Motor Speed R.P.M.                    | 850                 | 850                       | 850                       |
| Volts/Ph/Hz                           | 208/230/1/60        | 208/230/1/60              | 208/230/1/60              |
| F.L. Amps                             | 1.05                | 0.93                      | 2.80                      |
| <b>Outdoor Coil – Type</b>            | SPINE FIN™          | SPINE FIN™                | SPINE FIN™                |
| Rows – F.P.I.                         | 1 – 24              | 1 – 24                    | 1 – 24                    |
| Face Area (Sq. Ft.)                   | 24.93               | 30.8                      | 30.8                      |
| Tube Size (in.)                       | 3/8                 | 3/8                       | 3/8                       |



## Product Specifications

**Table 3. 5TTX5042 – 5TTX5060 (continued)**

| <b>Refrigerant</b>                                       |                 |                 |                 |
|--|-----------------|-----------------|-----------------|
| LBS. – R-454B (O.D. Unit) <sup>(a)</sup>                 | 5 LBS., 1 OZ    | 6 LBS., 10 OZ   | 5 LBS., 15 OZ   |
| Factory Supplied   | YES             | YES             | YES             |
| Valve Connection Size – (in.) O.D. Gas                   | 7/8             | 7/8             | 7/8             |
| Valve Connection Size – (in.) O.D. Liq.                  | 5/16            | 5/16            | 5/16            |
| Line Size – (in.) O.D. Gas <sup>(h)</sup> <sup>(i)</sup> | 7/8             | 7/8             | 1-1/8           |
| Line Size – (in.) O.D. Liq.                              | 5/16            | 5/16            | 5/16            |
| <b>Charging Specifications</b>                           |                 |                 |                 |
| Subcooling   | 10°F            | 10°F            | 10°F            |
| <b>Dimensions</b>  |                 |                 |                 |
|  | H X W X D       |                 |                 |
| Crated (in.)   | 48 x 35 x 38    | 56 x 35 x 38    | 56 x 35 x 38    |
| <b>Weight</b>  |                 |                 |                 |
| Shipping (lbs.)  | 246             | 307             | 302             |
| Net (lbs.)   | 212             | 257             | 252             |
| <b>Optional Accessories:</b>                             |                 |                 |                 |
| Anti-short Cycle Timer                                   | TAYASCT501A     | TAYASCT501A     | TAYASCT501A     |
| Evaporator Defrost Control                               | AY28X079        | AY28X079        | AY28X079        |
| Rubber Isolator Kit                                      | BAYISLT101      | BAYISLT101      | BAYISLT101      |
| Extreme Condition Mount Kit                              | BAYECMT004      | BAYECMT004      | BAYECMT004      |
| Start Kit  | BAYKSKT263      | BAYKSKT263      | BAYKSKT263      |
| Crankcase Heater Kit                                     | BAYCCHT301      | BAYCCHT301      | BAYCCHT301      |
| Seacoast Kit   | BAYSEAC001      | BAYSEAC001      | BAYSEAC001      |
| Low Ambient Kit  | BAYLOAM103      | BAYLOAM103      | —               |
| Service Valve Panel Cover                                | TAYSVPANL0046AA | TAYSVPANL0046AA | TAYSVPANL0046AA |
| Refrigerant Lineset <sup>(i)</sup>                       |                 |                 |                 |

<sup>(a)</sup> Certified in accordance with the Unitary Air-conditioner equipment certification program which is based on AHRI standard 210/240.

<sup>(b)</sup> Rated in accordance with AHRI standard 270.

<sup>(c)</sup> Calculated in accordance with N.E.C. Only use HACR circuit breakers or fuses.

<sup>(d)</sup> This value shown for compressor RLA on the unit nameplate and on this specification sheet is used to compute minimum branch circuit ampacity and max. fuse size. The value shown is the branch circuit selection current.

<sup>(e)</sup> Use start components only when compressor is found to enter locked rotor condition and will not start or when lights dim at compressor start." No means no start components. Yes means quick start kit components. PTC means positive temperature coefficient starter. Optional kit shown.

<sup>(f)</sup> Standard Air– Dry Coil– Outdoor.

<sup>(g)</sup> This value approximate. For more precise value see unit nameplate.

<sup>(h)</sup> Reference the outdoor unit ship-with literature for refrigerant piping length and lift guidelines. Reference the refrigerant piping software pub # 32-3312-xx or *Refrigerant Piping Manual for Small Split Cooling and Heat Pump Systems Application Guide* (SS-APG006\*-EN) for long line sets or specialty applications (xx denotes latest revision).

<sup>(i)</sup> The outdoor condensing units are factory charged with the system charge required for the outdoor condensing unit, ten (10) feet of tested connecting line, and the smallest rated indoor evaporative coil match. Always verify proper system charge via subcooling (TXV/EEV) or superheat (fixed orifice) per the unit nameplate.

<sup>(j)</sup> 25, 30, 35 and 50 foot linesets available. For a complete listing of lineset options available from equipment or supply stores, refer to the Trane Residential and Light Commercial Product Handbook.



# Sound Power Level

Table 4. Sound power level

| MODEL     | A-Weighted Sound Power Level [dB (A)] | Full Octave Sound Power(dB) |        |        |        |         |         |         |         |
|-----------|---------------------------------------|-----------------------------|--------|--------|--------|---------|---------|---------|---------|
|           |                                       | 63 Hz*                      | 125 Hz | 250 Hz | 500 Hz | 1000 Hz | 2000 Hz | 4000 Hz | 8000 Hz |
| 5TTX5018A | 73                                    | 79                          | 69     | 67     | 70     | 70      | 64      | 59      | 53      |
| 5TTX5024A | 71                                    | 78                          | 72     | 69     | 68     | 66      | 61      | 58      | 53      |
| 5TTX5030A | 73                                    | 79                          | 69     | 67     | 70     | 70      | 64      | 59      | 53      |
| 5TTX5036A | 71                                    | 78                          | 72     | 69     | 68     | 66      | 61      | 58      | 53      |
| 5TTX5042A | 71                                    | 78                          | 72     | 69     | 68     | 66      | 61      | 58      | 53      |
| 5TTX5048A | 71                                    | 81                          | 75     | 71     | 70     | 68      | 63      | 58      | 53      |
| 5TTX5060A | 71                                    | 81                          | 75     | 71     | 70     | 68      | 63      | 58      | 53      |

**Note:** Rated in accordance with AHRI Standard 270-2008 \*For reference only.



## Accessory Description and Usage

**Anti-Short Cycle Timer** — Solid state timing device that prevents compressor recycling until five (5) minutes have elapsed after satisfying call or power interruptions. Use in area with questionable power delivery, commercial applications, long lineset, etc.

**Evaporation Defrost Control** — SPST Temperature actuated switch that cycles the condenser off as indoor coil reaches freeze-up conditions. Used for low ambient cooling to 30°F with TXV.

**Rubber Isolators** — Five (5) large rubber donuts to isolate condensing unit from transmitting energy into mounting frame or pad. Use on any application where sound transmission needs to be minimized.

**Hard Start Kit** — Start capacitor and relay to assist compressor motor start-up. Use in areas with marginal power supply, on long linesets, low ambient conditions, etc.

**Extreme Condition Mount Kit** — Bracket kits to securely mount condensing unit to a frame or pad without removing any panels. Use in areas with high winds, or on commercial roof tops, etc.

### AHRI Standard Capacity Rating Conditions


AHRI Standard 210/240 Rating Conditions

1. Cooling 80°F DB, 67°F WB air entering indoor coil, 95°F DB air entering outdoor coil.
2. High Temperature Heating 47°F DB, 43°F WB air entering outdoor coil, 70°F DB air entering indoor coil.
3. Low Temperature Heating 17°F DB air entering indoor coil.
4. Rated indoor airflow for heating is the same as for cooling.

**AHRI Standard 270 Rating Conditions** — (Noise rating numbers are determined with the unit in cooling operations.) Standard Noise Rating number is at 95°F outdoor air.

## Model Nomenclature

### Outdoor Units






# Wiring Diagrams

**Figure 1. 018A – 048A models**

TO POWER SUPPLY PER UNIT NAMEPLATE AND LOCAL CODES



## LEGEND

|      |                              |
|------|------------------------------|
| CF   | FAN CAPACITOR                |
| CN   | WIRECONNECTOR                |
| CPR  | COMPRESSOR                   |
| CR   | RUN CAPACITOR                |
| CS   | STARTING CAPACITOR           |
| CSR  | CAPACITOR SWITCHING RELAY    |
| F    | INDOOR FAN RELAY             |
| HPCO | HIGH PRESSURE CUTOOUT SWITCH |
| LPCO | LOW PRESSURE CUTOOUT SWITCH  |
| IOL  | INTERNAL OVERLOAD PROTECTOR  |
| SM   | SYSTEM ON-OFF SWITCH         |
| MS   | COMPRESSOR MOTOR CONTACTOR   |
| ODA  | OUTDOOR ANTICIPATOR          |
| OFT  | OUTDOOR FAN THERMOSTAT       |
| ODS  | OUTDOOR TEMPERATURE SENSOR   |
| ODT  | OUTDOOR THERMOSTAT           |
| SC   | SWITCH OVER VALVE SOLENOID   |
| TDL  | DISCHARGE LINE THERMOSTAT    |
| TNS  | TRANSFORMER                  |

COLOR OF WIRE  
BK/BL


COLOR OF MARKER

|    |       |      |            |    |        |
|----|-------|------|------------|----|--------|
| BK | BLACK | RD   | RED        | OR | ORANGE |
| BL | BLUE  | WH   | WHITE      | GR | GREEN  |
| BR | BROWN | YL   | YELLOW     | PR | PURPLE |
| PK | PINK  | LTBL | LIGHT BLUE |    |        |

FOR CANADIAN INSTALLATIONS  
POUR INSTALLATIONS CANADIENNES

CAUTION: NOT SUITABLE FOR USE ON  
SYSTEMS EXCEEDING 150V-TO-GROUND  
ATTENTION: NE CONVIENT PAS AUX  
INSTALLATIONS DE PLUS DE 150 V A  
LA TERRE



PRINTED FROM DI57362P08 REV C




**Figure 2. 018A – 048A models**

**NOTES:**

1. IF ODT-B IS NOT USED. ADD JUMPER BETWEEN W2 & W3 AT AIR HANDLER. IF USED, ODT-B MUST BE MOUNTED REMOTE OF CONTROL BOX IN AN APPROVED WEATHER PROOF ENCLOSURE.
2. IF ODT-A IS NOT USED. ADD JUMPER BETWEEN W1 & W2 AT AIR HANDLER.
3. LOW VOLTAGE (24 V) FIELD WIRING MUST BE 18 AWG MIN.



**Figure 3. 060A models**



## LEGEND

|      |                             |
|------|-----------------------------|
| CF   | FAN CAPACITOR               |
| CN   | WIRE CONNECTOR              |
| CPR  | COMPRESSOR                  |
| CR   | RUN CAPACITOR               |
| CS   | STARTING CAPACITOR          |
| CSR  | CAPACITOR SWITCHING RELAY   |
| ODT  | OUTDOOR THERMOSTAT          |
| HPCO | HIGH PRESSURE CUTOFF SWITCH |
| LPCO | LOW PRESSURE CUTOFF SWITCH  |
| MS   | COMPRESSOR MOTOR CONTACTOR  |
| TNS  | TRANSFORMER                 |
| IOL  | INTERNAL OVERLOAD PROTECTOR |

COLOR OF WIRE  
BK/BL

COLOR OF MARKER

|    |       |    |        |    |        |
|----|-------|----|--------|----|--------|
| BK | BLACK | RD | RED    | OR | ORANGE |
| BL | BLUE  | WH | WHITE  | GR | GREEN  |
| BR | BROWN | YL | YELLOW | PR | PURPLE |
| PK | PINK  |    |        |    |        |

FOR CANADIAN INSTALLATIONS  
POUR INSTALLATIONS CANADIENNES

CAUTION: NOT SUITABLE FOR USE ON  
SYSTEMS EXCEEDING 150V-TO-GROUND  
ATTENTION: NE CONVIENT PAS AUX  
INSTALLATIONS DE PLUS DE 150 V A  
LA TERRE

PRINTED FROM DI62656P01 REVA



## Wiring Diagrams


**Figure 4. 060A models**

**NOTES:**

1. IF ODT-B IS NOT USED. ADD JUMPER BETWEEN W2 & W3 AT AIR HANDLER.  
IF USED, ODT-B MUST BE MOUNTED REMOTE OF CONTROL BOX IN AN APPROVED WEATHER PROOF ENCLOSURE.
2. IF ODT-A IS NOT USED. ADD JUMPER BETWEEN W1 & W2 AT AIR HANDLER.
3. LOW VOLTAGE (24 V) FIELD WIRING MUST BE 18 AWG MINIMUM.
4. USE COPPER CONDUCTORS ONLY!

**LEGEND**


|  |      |   |
|--|------|---|
|  | 24 V | FACTORY WIRING                            |
|  | 24 V | FIELD WIRING                              |
|  | 24 V | FIELD INSTALLED LINE                      |
|  | 24 V | FACTORY WIRING                            |
|  |      | MAGNETIC COIL                             |
|  |      | GROUND                                    |
|  |      | JUNCTION                                  |
|  |      | CAPACITOR                                 |
|  |      | WIRE NUT OR CONNECTOR                     |
|  |      | TERMINAL                                  |
|  |      | TRANSFORMER                               |
|  |      | TERMINAL BLOCK/BOARD                      |
|  |      | RELAY CONTACT (N.O.)                      |
|  |      | RELAY CONTACT (N.C.)                      |
|  |      | THERMISTOR                                |
|  |      | TEMP ACTUATED SWITCH                      |
|  |      | INTERNAL OVERLOAD PROTECTION              |
|  |      | PRESSURE ACTUATED SWITCH                  |
|  |      | RESISTOR OR HEATING ELEMENT               |
|  |      | MOTOR WINDING                             |
|  |      | POL. PLUG FEMALE HOUSING (MALE TERMINALS) |
|  |      | POL. PLUG MALE HOUSING (FEMALE TERMINALS) |



PRINTED FROM DI62656P01 REVA

# Dimensional Data

**Figure 5. Dimensional data**



**Table 5. Unit dimensions**

| Model     | Base | A                    | B               | C               | D   | E    | F              | G             | H              | J             | K                  |
|-----------|------|----------------------|-----------------|-----------------|-----|------|----------------|---------------|----------------|---------------|--------------------|
| 5TTX5018A | 3    | 1077<br>(42.40)      | 829<br>(32-5/8) | 756<br>(29-3/4) | 3/4 | 5/16 | 143<br>(5-5/8) | 92<br>(3-5/8) | 210<br>(8-1/4) | 79<br>(3-1/8) | 651<br>(25-3/5)    |
| 5TTX5024A | 3    | 975<br>(38.40)       | 829<br>(32-5/8) | 756<br>(29-3/4) | 3/4 | 5/16 | 143<br>(5-5/8) | 92<br>(3-5/8) | 210<br>(8-1/4) | 79<br>(3-1/8) | 651<br>(25-3/5)    |
| 5TTX5030A | 3    | 1077<br>(42.40)      | 829<br>(32-5/8) | 756<br>(29-3/4) | 3/4 | 5/16 | 143<br>(5-5/8) | 92<br>(3-5/8) | 210<br>(8-1/4) | 79<br>(3-1/8) | 651<br>(25-3/5)    |
| 5TTX5036A | 3    | 975<br>(38.40)       | 829<br>(32-5/8) | 756<br>(29-3/4) | 3/4 | 5/16 | 143<br>(5-5/8) | 92<br>(3-5/8) | 210<br>(8-1/4) | 79<br>(3-1/8) | 651<br>(25-3/5)    |
| 5TTX5042A | 4    | 1103.02<br>(43.435)  | 946<br>(37-1/4) | 870<br>(34-1/4) | 7/8 | 5/16 | 152<br>(6)     | 98<br>(3-7/8) | 219<br>(8-5/8) | 86<br>(3-3/8) | 668.024<br>(26.31) |
| 5TTX5048A | 4    | 1307.024<br>(51.435) | 946<br>(37-1/4) | 870<br>(34-1/4) | 7/8 | 5/16 | 152<br>(6)     | 98<br>(3-7/8) | 219<br>(8-5/8) | 86<br>(3-3/8) | 668.024<br>(26.31) |
| 5TTX5060A | 4    | 1307.024<br>(51.435) | 946<br>(37-1/4) | 870<br>(34-1/4) | 7/8 | 5/16 | 152<br>(6)     | 98<br>(3-7/8) | 219<br>(8-5/8) | 86<br>(3-3/8) | 668.024<br>(26.31) |



# Mechanical Specification Options

## General

The outdoor condensing units are factory charged with the system charge required for the outdoor condensing unit, ten (10) feet of tested connecting line, and the smallest rated indoor evaporative coil match. This unit is designed to operate at outdoor ambient temperatures as high as 115°F. Cooling capacities are matched with a wide selection of air handlers and furnace coils that are AHRI certified. The unit is certified to 60335-2-40. Exterior is designed for outdoor application.

## Casing

Unit casing is constructed of heavy gauge, galvanized steel and painted with a weather-resistant powder paint finish. The corner panels are prepainted. All panels are subjected to our 1,000 hour salt spray test.

## Refrigerant Controls

Refrigeration system controls include condenser fan, compressor contactor and low and high pressure switches. A factory supplied, field installed liquid line drier is standard.

## Compressor

The compressor features internal over temperature and pressure protection. Other features include: Centrifugal oil pump and low vibration and noise.

## Condenser Coil

The outdoor coil provides low airflow resistance and efficient heat transfer. The coil is protected on all four sides by louvered panels.

## Low Ambient Cooling

As manufactured, this system has a cooling capacity to 55°F. The addition of an evaporator defrost control permits operation to 40°F. The addition of an evaporator defrost control with TXV permits low ambient cooling to 30°F.

The addition of the BAYLOAM107A low ambient kit permits ambient cooling to 20°F.

**Thermostats** – Cooling only and heat/cooling (manual and automatic change over). Sub-base to match thermostat and locking thermostat cover.





Trane - by Trane Technologies (NYSE: TT), a global innovator - creates comfortable, energy efficient indoor environments for commercial and residential applications. For more information, please visit [trane.com](http://trane.com) or [tranetechnologies.com](http://tranetechnologies.com).



The AHRI Certified mark indicates Trane U.S. Inc. participation in the AHRI Certification program. For verification of individual certified products, go to [ahridirectory.org](http://ahridirectory.org).

Trane has a policy of continuous data improvement and it reserves the right to change design and specifications without notice. We are committed to using environmentally conscious print practices.