

 CAUTION

USE COPPER CONDUCTORS ONLY!
UNIT TERMINALS ARE NOT DESIGNED
TO ACCEPT OTHER TYPES OF
CONDUCTORS.
FAILURE TO DO SO MAY CAUSE
DAMAGE TO THE EQUIPMENT.

THIS DRAWING IS ISSUED BY EATON AND SHALL NOT BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM, WITHOUT THE WRITTEN PERMISSION OF EATON. DRAWN BY: T. DIERDREY DATE: 05-09-08 REVISIONS: -- DATE: 05-09-08 BY: SIMPLA TO: 2307-3960 PRO/DET: TAL		FILE NUMBER: 2307-3969 DRAWING NUMBER: 2307-4394 SHEET: 1 OF 5 REV: C	
ROOT/TO: PAK KAGED AIR CONDITIONER SCHEMATIC WIRING DIAGRAM POWER IN: 208V 3PH 4W POWER IN: 208V 3PH 4W 20 - 60 TON 5.0 HP W/ SUPPLY AIR VARIABLE FREQUENCY DRIVE			