



TRANE

Date:04-03-96

HERMETIC CENTRIFUGAL LIQUID CHILLER

CENTRAVAC[®]
FIELD CONNECTION WIRING
CVHE,CVHF,CVHG

DRAWING NUMBER
2307-5218

REV
A

1. ALWAYS LOCK OUT AND TAG THE CHILLER BEFORE SERVICING. NEVER ATTEMPT TO SERVICER THE CHILLER WHILE IT IS RUNNING. NEVER ATTEMPT TO SERVICER THE CHILLER WHILE IT IS RUNNING. NEVER ATTEMPT TO SERVICER THE CHILLER WHILE IT IS RUNNING.
2. THE CHILLER IS EQUIPPED WITH A SAFETY SWITCH. THE SAFETY SWITCH MUST BE OPENED BEFORE SERVICING THE CHILLER. NEVER ATTEMPT TO SERVICER THE CHILLER WHILE IT IS RUNNING.
3. THE CHILLER IS EQUIPPED WITH A SAFETY SWITCH. THE SAFETY SWITCH MUST BE OPENED BEFORE SERVICING THE CHILLER. NEVER ATTEMPT TO SERVICER THE CHILLER WHILE IT IS RUNNING.
4. THE CHILLER IS EQUIPPED WITH A SAFETY SWITCH. THE SAFETY SWITCH MUST BE OPENED BEFORE SERVICING THE CHILLER. NEVER ATTEMPT TO SERVICER THE CHILLER WHILE IT IS RUNNING.
5. THE CHILLER IS EQUIPPED WITH A SAFETY SWITCH. THE SAFETY SWITCH MUST BE OPENED BEFORE SERVICING THE CHILLER. NEVER ATTEMPT TO SERVICER THE CHILLER WHILE IT IS RUNNING.
6. THE CHILLER IS EQUIPPED WITH A SAFETY SWITCH. THE SAFETY SWITCH MUST BE OPENED BEFORE SERVICING THE CHILLER. NEVER ATTEMPT TO SERVICER THE CHILLER WHILE IT IS RUNNING.
7. THE CHILLER IS EQUIPPED WITH A SAFETY SWITCH. THE SAFETY SWITCH MUST BE OPENED BEFORE SERVICING THE CHILLER. NEVER ATTEMPT TO SERVICER THE CHILLER WHILE IT IS RUNNING.
8. THE CHILLER IS EQUIPPED WITH A SAFETY SWITCH. THE SAFETY SWITCH MUST BE OPENED BEFORE SERVICING THE CHILLER. NEVER ATTEMPT TO SERVICER THE CHILLER WHILE IT IS RUNNING.
9. THE CHILLER IS EQUIPPED WITH A SAFETY SWITCH. THE SAFETY SWITCH MUST BE OPENED BEFORE SERVICING THE CHILLER. NEVER ATTEMPT TO SERVICER THE CHILLER WHILE IT IS RUNNING.
10. THE CHILLER IS EQUIPPED WITH A SAFETY SWITCH. THE SAFETY SWITCH MUST BE OPENED BEFORE SERVICING THE CHILLER. NEVER ATTEMPT TO SERVICER THE CHILLER WHILE IT IS RUNNING.

WARNING

HAZARDOUS VOLTAGE
DISCONNECT ALL ELECTRICAL POWER
INCLUDING REMOTE DISCONNECTS
BEFORE SERVICING. NEVER ATTEMPT
TO SERVICER THE CHILLER WHILE IT IS
RUNNING. NEVER ATTEMPT TO SERVICER
THE CHILLER WHILE IT IS RUNNING.

CAUTION

USE COPPER CONDUCTORS ONLY.
UNIT TERMINALS ARE NOT DESIGNED
TO ACCEPT OTHER TYPES OF
CONDUCTORS.
FAILURE TO DO SO MAY CAUSE
DAMAGE TO THE EQUIPMENT.

