

NOTES:

1 WIRING SHOWN IS FOR 230V. FOR 208V MOVE ALL WIRES FROM 230V TERMINAL TO 208V TERMINAL ON TNS1.

2 WIRING SHOWN IS FOR 230V. FOR 208V MOVE ALL WIRES FROM 230V TERMINAL TO 208V TERMINAL ON TNS2.

8 FUSE, FUSE, RELAY, XFR, CAPACITOR, CFS, CFS AND ASSOCIATED WIRES ARE ONLY USED WITH POWER EXHAUST OPTION.

11 WIRING SHOWN IS FOR OPTIONAL COMMUNICATION INTERFACE. COMMUNICATION WIRES FROM BMS TO TCI/LCI ARE TO BE WIRE TIED TO BOTTOM OF THE CONTROL BOX. SEE TCI/LCI LITERATURE FOR SWITCH SETTINGS.

12 FUSE, FUSE, FUSE AND SWITCH SRD ARE USED FOR OPTIONAL FACTORY POWER CONVENIENCE OUTLET. WIRES 400A AND 401A ARE CONNECTED TO FACTORY SUPPLIED DISCONNECT SWITCH.

METAL PLATE 11 X 17

IMPORTANT!
DO NOT ENERGIZE
UNIT UNTIL CHECK-OUT
AND START-UP PROCEDURE
HAS BEEN COMPLETED

TRANS

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

REPLACES

FILE NUMBER

2309-3263

SHEET 1 OF 2

CONTROL BOX CONNECTION FOR

TC 27.5-35 TON 208-230 VOLT

CONSTANT VOLUME

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

SHEET 1 OF 2

WARNING

HAZARDOUS VOLTAGE!
DISCONNECT ALL ELECTRIC POWER
INCLUDING REMOTE DISCONNECTS
BEFORE SERVICING.
FAILURE TO DISCONNECT POWER
BEFORE SERVICING CAN CAUSE SEVERE
PERSONAL INJURY OR DEATH.

AVERTISSEMENT

VOLTAGE HASARDEUX!
DECONNECTEZ TOUTES LES SOURCES
ELECTRIQUES INCLUANT LES
DISJONCTEURS SITUES A DISTANCE
AVANT D'EXECUTER L'ENTRETIEN.
ELECTRIQUE AVANT D'EXECUTER
L'ENTRETIEN PEUT ENTRAINER DES
BLESURES CORPORELLES SEVERES
OU LA MORT.

CAUTION

USE COPPER CONDUCTORS ONLY!
UNIT TERMINALS ARE NOT DESIGNED
TO ACCEPT OTHER TYPES OF
CONDUCTORS.
FAILURE TO DO SO MAY CAUSE
DAMAGE TO THE EQUIPMENT.

