

2 — 5 Ton YCY024 - 060G

XL 1400 Convertible Pkg. Gas/Electric

Specifications: XL 1400 - Single Phase


		Capacity	Capacity			Unc	rated			
Model	Power	Cooling	Htg.Outpu	ıt		Dim	n. (in.)		Mfg.	Shipping
Number	Supply	(BTUH)	(BTUH)	SEER	AFUE(%)	н	Ŵ	L	Plant	Weight
YCY024G1L0A	208/230/1/60	24,000	30 or 37	14.0	80.0	29	36	64	FS/200	444
YCY024G1M0A	208/230/1/60	24,000	44 or 53	14.0	80.0	29	36	64	FS/200	455
YCY030G1L0A	208/230/1/60	30,600	31 or 38	13.0	80.0	29	36	64	FS/200	474
YCY030G1M0A	208/230/1/60	30,600	44 or 55	13.0	80.0	29	36	64	FS/200	485
YCY036G1M0A	208/230/1/60	36,000	45 or 57	14.0	80.0	29	36	64	FS/200	508
YCY036G1H0A	208/230/1/60	36,000	61 or 72	14.0	80.0	29	36	64	FS/200	513
YCY042G1M0A	208/230/1/60	41,500	65 or 78	14.0	80.0	29	36	64	FS/200	513
YCY048G1H0A	208/230/1/60	49,000	73 or 95	14.4	80.0	33	45	65	FS/200	639
YCY060G1M0A	208/230/1/60	61,000	72 or 96	13.0	80.0	33	45	65	FS/200	659

Features:

- Variable Speed ECM motor with ramped start and quiet operation
- *Exclustive* Comfort -R[™] enhanced cooling/dehumidification mode (see chart)
- Two-stage gas heat for heating comfort
- Side electrical service access for high and low voltage
- Sloped composite no-rust drain pan
- All foil faced washable insulation
- Coil-Sav'R Lexan® grille
- Exclusive **trim ring** on top discharge fan grille
- Powder paint and Weatherguard™ coated screws for a quality apperance that lasts


- Exclusive **Climatuff**[®] high efficiency compressor
- Uni-Curb that fits all sizes 2-5 tons • Common cabinetry across lines
- (G/E, Clg.) and across efficiency tiers • Water-Shed no leak one piece base pan
- Two-stage direct spark integrated ignition control
- Two-speed combustion blower
- Ships for horizontal application; easily convertible to downflow
- Refrigerant line filter
- High efficiency outdoor fan motor with polarized plug
- UL Listed
- Compressor IOL protection

- Standard operations to 55°F as manufactured
- Low ambient cooling to 0°F with accessories BAYLOAM011A, BAYLOAM323A
- Optional In-Filter[™] filter rack fits inside unit
- 10-year limited compressor and oudoor coil warranty, 20-year limited heat exchanger warranty, 5-years on other parts (Residential Use Single Phase Only)
- Optional extended warranties






Exclustive Comfort -R[™] enhanced cooling/dehumidification mode







XL 1400 Convertible Pkg. Gas/Electric

Accessories:

Model	Description		Mfg.	Shipping
Number Extended Warranties	Description (1 yr - 5 yr - 10 yr - See Extended Warranty S	Used With	Plant	Weight
	(See Control Section)	ection)		
Controls		YCY-G Models	FS/200	74
BAYCURB030A	Roof Curb (Flat Roof)@(Universal)			
BAYCURB038A	Roof Curb (Flat Roof)@(Universal)Acousti-Curb	YCY-G Models	FS/200	74
BAYCURB033A	Roof Curb (Flat Roof)@⑦ Acousti-Curb	YCY024-042G	FS/200	88
BAYCURB034A	Roof Curb (Flat Roof)@® Acousti-Curb	YCY048,060G	FS/200	100
BAYINDK002A**	Insulated Deck Pan for C Cabinet	BAYCURB033A		28
BAYINDK003A***	Insulated Deck Pan for D Cabinet	BAYCURB034A		30
BAYECON054B	0-100% Mod. Econ. w/Bar Relief 1346	YCY024-042G	FS/200	50
BAYECON055B	0-100% Mod. Econ. w/Bar Relief(134)6	YCY048-060G	FS/200	65
BAYECON073A	0-100% Mod. Econ Horizontal	YCY-G Models	FS/200	85
BAYSTAT023	Remote Potentiometer	All Economizers		1
BAYENTH001A	Enthalpy Control (Solid State)	YCY-G Models	FS/200	2
BAYDMPR040A	0-25% Manual Fresh Air Damper 14	YCY024-042G	FS/200	6
BAYDMPR041A	0-25% Manual Fresh Air Damper 14	YCY048-060G	FS/200	8
BAYFLTR013A	Filter Frame (20x25x1" filter not incl)	YCY024,042G	FS/200	6
BAYFLTR014A	Filter Frame (3-10x24x1" filter not incl)	YCY048-060G	FS/200	9
BAYFLTR018A	Filter Frame (1-20x25x2" filter not incl)	YCY024-042G	FS/200	9
BAYFLTR019A	Filter Frame ⁽⁾ (2-16x25x2" filter not incl)	YCY048-060G	FS/200	9
BAYLOAM011A	Evap. Defrost Control Kit	YCY-G Models	ΤY	5
BAYLOAM323A	Head Pressure Control 6 10	YCY-G Models	FS/200	5
BAYMOTR307A	Low Ambient Motor (208/230)	YCY-G Models	FS	20
BAYLPKT024B	LP Conversion Kit	YCY-G Models	FS/200	2
BAYLPSS002A	LP Conversion Kit with SS Burners	YCY-G Models	FS/200	10
BAYDUCT004A	12" Round Duct Adapters (2 Per Box)	YCY024-042G	FS/200	5
BAYDUCT005A	14" Round Duct Adapter (1 Per Box)	YCY024-042G	FS/200	3
BAYLIFT002B	Lifting Lug Kit	YCY-G Models	FS/200	5
BAYASCT001	Anti-Short Cycle Timer	YCY-G Models	FS/200	1
BAYCCHT003A	Crankcase Heater (230v)®	YCY024-048G1	FS/200	2
BAYCCHT202A	Crankcase Heater (230v)	YCY060G1	FS/200	2
-				

0 Must use filter frame when economizer/fresh air kit is used.

Must use filter frame when economizer/fresh air kit is used.
Ships knocked down.
Dry bulb control standard with economizer.
Downflow Only.
Use low ambient motor on YCY024-042G. Not required on YCY048-060G1
2-Stage thermostat provides additional energy savings if simultaneous economizer and compressor operation is expected.
Full perimeter curb for YCY024,042G
Full perimeter curb for YCY048,060G
It is the responsibility of the installing dealer to properly size the ductwork for each specific application
Low ambient cooling requires crankcase heater (BAYCCHT***A)
* Currently shipped with BAYCURB038A
***Currently shipped with BAYCURB033A

***Currently shipped with BAYCURB034A